

## Materials Index

### A

Additively manufactured materials:  
13021006 pg. 2  
Aerogel: 13021007 pg. 1; 13021022 pg. 1  
Airplane motors: 13021017 pg. 1  
Aluminum: 13021017 pg. 3; 13021032 pg. 7  
Alumina: 13021031 pg. 6  
Aluminum alloys: 13021005 pg. 2;  
13021006 pg. 1; 13021009 pg. 3  
Austenitic stainless steels  
AISI 304: 13021002 pg. 1  
AISI 316L: 13021001 pg. 1; 13021002 pg. 1;  
13021032 pg. 7

### B

BaZrO<sub>3</sub>: 13021013 pg. 1  
Bismuth compounds  
BSCCO: 13021010 pg. 2  
Bi-metal conductor: 13021036 pg. 1

### C

Cables  
Conductor on round core (CORC):  
13021017 pg. 6  
Power: 13021015 pg. 1  
Capacitors: 13021018 pg. 3; 13021026 pg. 4  
Carbon fiber reinforced plastic: 13021023 pg. 5  
Charge readout planes: 13021032 pg. 1  
Coated conductors: 13021011 pg. 1;  
13021012 pg. 1; 13021013 pg. 1;  
13021014 pg. 1; 13021016 pg. 3  
Copper: 13021005 pg. 2; 13021017 pg. 3;  
13021031 pg. 3  
Copper-clad Li: 13021036 pg. 1  
Cryogel: 13021022 pg. 7  
Cryogenic hydrogen: 13021022 pg. 1;  
13021023 pg. 1; 13021025 pg. 1  
Cryogenic converters: 13021018 pg. 1;  
13021026 pg. 1  
Cryostats: 13021030 pg. 3  
Current leads: 13021014 pg. 1; 13021016 pg. 1  
Cynate ester: 13021003 pg. 1; 13021003 pg. 3

### E

Electric engine: 13021023 pg. 1  
Electric powertrain: 13021023 pg. 2  
Electric propulsion: 13021024 pg. 1  
Epoxy: 13021003 pg. 1; 13021004 pg. 1;  
13021008 pg. 1

### F

Fe-based superconductor: 13021035 pg. 1  
Foam glass: 13021007 pg. 2

### G

G10 plate: 13021021 pg. 6  
G-10-Fe: 13021004 pg. 1  
GaN: 13021026 pg. 1; 13021029 pg. 1  
Gate injection transistor (GIT): 13021029 pg. 1  
Glass-fiber epoxy composite: 13021008 pg. 1  
Glass-fiber reinforced plastics: 13021003 pg. 1  
Graphite: 13021034 pg. 1

### H

Helium cryoplant: 13021030 pg. 3  
High electron mobility transistor (HEMT):  
13021018 pg. 4; 13021026 pg. 1;  
13021029 pg. 1

### I

IGBT module: 13021018 pg. 4; 13021028 pg. 1  
Inconel: 13021005 pg. 2  
Inductors: 13021026 pg. 4

### L

Liquid hydrogen: 13021022 pg. 1; 13021023 pg. 1;  
13021024 pg. 1; 13021025 pg. 1  
Liquified natural gas: 13021022 pg. 3;  
13021025 pg. 1

### M

Martensite stainless steel: 13021033 pg. 1  
MEMS switch: 13021027 pg. 2  
Mercury: 13021010 pg. 4  
Metal matrix composite  
Aluminum-based MMCs A6061-RAM2:  
13021006 pg. 1  
MgB<sub>2</sub>: 13021010 pg. 2  
MilliKelvin platform: 13021030 pg. 1  
MOSFET: 13021018 pg. 4  
Motor: 13021009 pg. 2; 13021017 pg. 1

### N

Nanocomposites: 13021013 pg. 1  
Nb<sub>3</sub>Ge: 13021010 pg. 4  
Nb<sub>3</sub>Sn: 13021010 pg. 2  
NbTi: 13021010 pg. 2  
Nylon: 13021032 pg. 6



**P**

PEEK: 13021032 pg. 6

Polyetheramine: 13021003 pg. 1

Polymer based composite

Nylon-based PMC PA840-GSL:  
13021006 pg. 1

Power converters: 13021018 pg. 1;  
13021026 pg. 1; 13021028 pg. 3

Power electronics: 13021028 pg. 2;  
13021029 pg. 2

Pressure transducer: 13021033 pg. 1

**Q**

Quantum computers: 13021027 pg. 1;  
13021030 pg. 1

**R**

Rare earth (RE) compounds

La-Ba-Cu-O: 13021010 pg. 6

RE-123: 13021010 pg. 2; 13021011 pg. 1;  
13021012 pg. 1; 13021013 pg. 1;  
13021014 pg. 3; 13021016 pg. 1;  
13021017 pg. 6; 13021021 pg. 5

Resin

Diglycidyl ether of bisphenol A (DGEBA):  
13021003 pg. 2

Room temperature superconductors

LK-99: 13021010 pg. 2

Lu-N-H: 13021010 pg. 2

**S**

Samarium-Cobalt: 13021031 pg. 7

Scalmalloy: 13021005 pg. 2

Semiconductors: 13021026 pg. 3; 13021028 pg. 1

Silicon: 13021018 pg. 1

Soft magnetic composites: 13021004 pg. 1

Sulfur hydride: 13021010 pg. 10

Superconducting magnet: 13021021 pg. 1

Superconducting motor: 13021020 pg. 2

Superconducting rotor: 13021020 pg. 3

Synchronous machine: 13021017 pg. 4

**T**

Titanium alloy: 13021005 pg. 2

**W**

Wide band gap devices: 13021018 pg. 1

**Y**

Yttrium compound

YBCO: 13021010 pg. 2; 13021011 pg. 1;  
13021012 pg. 1; 13021013 pg. 1;  
13021014 pg. 3; 13021016 pg. 1;  
13021019 pg. 1; 13021021 pg. 5

## Subject Index

### A

Additive manufacturing: 13021005 pg. 1

Ashby method: 13021036 pg. 2

### C

Cables, superconductive

Power cables with gaseous insulation:

13021015 pg. 4

Power: 13021015 pg. 1

Cable design: 13021015 pg. 3

Capacitance: 13021026 pg. 4; 13021029 pg. 4

Coefficient of linear expansion: 13021033 pg. 7;  
13021036 pg. 6

Coefficient of friction: 13021032 pg. 6

Cold gas spray: 13021005 pg. 2

Cooling system design: 13021030 pg. 6

Conductivity modulation mode: 13021029 pg. 4

Contact resistance: 13021027 pg. 7

Converter efficiency: 13021026 pg. 5

Core loss: 13021004 pg. 4

Critical current

Re-123: 13021011 pg. 6; 13021016 pg. 5

Critical current density: 13021013 pg. 5

Critical surface: 13021010 pg. 3

Critical temperature: 13021010 pg. 4;

13021010 pg. 6; 13021010 pg. 10;

13021013 pg. 4

Cryotreatment of metals: 13021033 pg. 3

Curing conditions: 13021003 pg. 3

### D

DeLong's diagram: 13021002 pg. 4

Dielectric loss: 13021026 pg. 4

Direct energy deposition: 13021005 pg. 2

Drive voltages: 13021027 pg. 5

### E

Elastic modulus: 13021006 pg. 5

Electrical conductivity

Aluminum: 13021036 pg. 3

Al alloys: 13021005 pg. 6

Copper: 13021036 pg. 3

Inconel: 13021005 pg. 6

Lithium: 13021036 pg. 3

Magnesium: 13021036 pg. 3

Ti alloys: 13021005 pg. 6

Electrical faults: 13021015 pg. 2

Electrical isolator: 13021015 pg. 5

Electrical machines: 13021017 pg. 3

Electric transportation: 13021015 pg. 1;

13021018 pg. 1

Electrical resistivity: 13021009 pg. 3;

13021036 pg. 5

Electron density of states: 13021010 pg. 5

Elongation

Stainless steel 316LN: 13021002 pg. 4

### F

Fatigue crack growth rate

Stainless steel 316L: 13021001 pg. 3

Fatigue testing: 13021001 pg. 3

Flux pinning force: 13021013 pg. 5

Fracture toughness

Stainless steel 304: 13021002 pg. 5

Stainless steel 316L: 13021002 pg. 5

Friction coefficient test: 13021032 pg. 4

### G

Gama-ray irradiation: 13021003 pg. 4

### H

Hardness

Copper: 13021005 pg. 8

Heat capacity

Al alloys: 13021005 pg. 7

Cu: 13021005 pg. 7

Inconel: 13021005 pg. 7

Ti alloys: 13021005 pg. 7

Heat flux: 13021021 pg. 1

Heat load: 13021014 pg. 6

Hydrogen storage density: 13021022 pg. 7;

13021024 pg. 6

Hydrogen storage tank design: 13021024 pg. 2;

13021024 pg. 7

### I

Inductance: 13021020 pg. 6

Interlaminar shear strength: 13021003 pg. 6

### L

Layered structure: 13021010 pg. 8

### M

Magnet current: 13021021 pg. 8

Magnet voltage: 13021021 pg. 8

Magnetic flux: 13021019 pg. 6

Magnetic field distribution: 13021021 pg. 4

Magnetic field shielding: 13021019 pg. 5

Magnetic field strength: 13021021 pg. 9  
 Magnetic hysteresis loop: 13021004 pg. 3  
 Magnetization: 13021004 pg. 3;  
     13021010 pg. 12; 13021034 pg. 3  
 Magneto optic imaging: 13021011 pg. 6  
 Magnetoresistance: 13021034 pg. 7  
 Meissner effect: 13021019 pg. 3  
 Microstructure  
     Aerogel: 13021007 pg. 3  
 Aluminum alloys: 13021005 pg. 4  
     Copper: 13021005 pg. 3; 13021005 pg. 9  
     Epoxy: 13021004 pg. 3; 13021008 pg. 5  
     Fe-based superconductor: 13021035 pg. 3  
 REBCO: 13021011 pg. 4; 13021012 pg. 6  
 Titanium alloys: 13021005 pg. 4  
 Motor performances: 13021017 pg. 7

## N

Nonlinear Conjugate Gradient (NCG) method:  
     13021009 pg. 3

## O

On-state resistance: 13021026 pg. 3  
 Overshoot voltage: 13021028 pg. 4

## P

Persistent switching: 13021028 pg. 5  
 Process intensification: 13021025 pg. 4  
 Proof stress: 13021002 pg. 3  
 Proton irradiation: 13021019 pg. 7  
 Power loss: 13021009 pg. 4  
 Power profile: 13021024 pg. 3

## R

Radio blackout: 13021021 pg. 1  
 Raman spectra: 13021012 pg. 6; 13021034 pg. 2  
 Reduction in area: 13021002 pg. 4  
 Residual resistivity ratio  
     Aluminum: 13021017 pg. 4  
 Resistance  
     Copper: 13021005 pg. 8  
 Resistance vs. temperature: 13021017 pg. 3;  
     13021035 pg. 3  
 Resistivity: 13021017 pg. 3; 13021034 pg. 6

## S

Saturation magnetization: 13021004 pg. 3  
 Selective laser melting: 13021005 pg. 2  
 Shear strength  
     Inter laminar: 13021003 pg. 6  
 Spaceflights: 13021016 pg. 1; 13021019 pg. 1  
 Specific heat: 13021035 pg. 6; 13021036 pg. 7  
 Spin waves: 13021034 pg. 1

Stator bearing design: 13021023 pg. 4  
 Stress-strain curves  
     Aerogels: 13021007 pg. 6  
     Epoxy: 13021008 pg. 3  
     Glass-fiber reinforced composite: 13021008 pg. 3  
 Surface roughness: 13021032 pg. 6  
 Suutala diagram: 13021002 pg. 3  
 Switching loss: 13021018 pg. 6; 13021026 pg. 3

## T

Tensile properties  
     Aerogel: 13021007 pg. 7  
     Aluminum alloys: 13021006 pg. 5  
     Austenitic stainless steel: 13021001 pg. 2;  
         13021002 pg. 4  
     Copper: 13021036 pg. 4  
     Epoxy: 13021008 pg. 4  
     Stainless steel 316L: 13021002 pg. 4  
     Stainless steel 316 LN: 13021002 pg. 4  
 Thermal conductivity  
     Aluminum: 13021036 pg. 6  
     Aluminum alloys: 13021005 pg. 6  
     Beryllium: 13021036 pg. 6  
     Copper: 13021005 pg. 8; 13021036 pg. 6  
     Coated conductor: 13021014 pg. 3; 13021014 pg. 6  
     Foam glass: 13021007 pg. 5  
     Inconel: 13021005 pg. 6  
     Lithium: 13021036 pg. 6  
     Ti alloys: 13021005 pg. 6  
 Thermal contractions  
     Alumina: 13021031 pg. 6  
     Copper: 13021031 pg. 4  
     Samarium-Cobalt: 13021031 pg. 7  
 Thermal cycling: 13021014 pg. 8  
 Thermal expansion  
     Al alloys: 13021005 pg. 7  
     Copper: 13021005 pg. 7; 13021031 pg. 5;  
         13021036 pg. 6  
     Inconel: 13021005 pg. 7  
     Ti alloys: 13021005 pg. 7  
 Thermal modeling: 13021030 pg. 7

## V

Viscosity: 13021003 pg. 7  
 Voltage rise: 13021016 pg. 6

## Y

Young's modulus  
     Copper: 13021036 pg. 4  
     Epoxy composite: 13021008 pg. 4

## Z

Zero emission aviation: 13021024 pg. 1